



Technical Data

ROLLER COAT :

Product Description :

Roller coat is the most popular exterior grade water repellent coating that offers outstanding resistance and vapour permeability properties. Formulated from quartz powder with a maximum grain size of 0.3mm

Special Feature :

The product contains acrylic polymer & special biocides in water dispersion, which guarantee excellent resistance to climatic condition, leave unaltered the transpiration of the surface, and prevent the development of moulds and algae. Furthermore, the product is resistant to acids and frost haw cycles. It keeps the masonry always dry and improves energy saving; it also assures the best hygienic conditions and house comfort. It can be used as finish coat both on high- diffusion plasters and on all wall surfaces. It is odourless, non-flammable and environmentally friendly.

Recommended use :

To be used on exterior surface. Can be used on interior surfaces of cement plaster, gypsum board and woodwork. Interior and exterior walls of prestigious buildings, recommended for high diffusion plasters.

Comments :

Theoretical spreading rate – Depending on thickness applied.

Product Thickness and spreading rate :

Product Thickness: 0.8mm – 1.0mm

Spreading(Covering): 300 sq.ft. per bag

Surface preparation : The surfaces must be completely dry and mature, new plaster must be mature at least 30day in order to consent the carbonization process. Clean the surfaces to be decorated and remove loose or flaking materials. In case of new plasters, make sure the substrate is thoroughly dry. In case of restoration works Rectify large water infiltration or leaks. Allow the wall to dry, use Cemplast for patch repairing & primer. Allow the primer to dry for 12 hours then apply the finishing products.

Condition during Application

The temperature of the substrate should be 5oC minimum and 36oC maximum (relative humidity not higher than 80%). No seepage on the surface, and weather must be dry during application.

Application Methods

Short hair flat brush, medium- grain sponge, cloth pad & Primer

Storage :

The product must be stored in accordance with national regulations. The product must be kept in a cool and well-ventilated place, protected from heat and direct sunlight. Containers must be kept tightly closed.

Handling : Handle with care

Packing Size : 30 Kg's Packing may vary from place to place according to local requirements.

Health and safety :

Please observe the precautionary notices displayed on the container. Use under well ventilated conditions. Avoid skin contact. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. Eyes should be well flushed with water and medical attention sought immediately. _____